

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

*** Section 1 - Chemical Product and Company Identification ***

Product Identifier:

Preact Galvanizing Flux Solution SF-L, SF-LB, SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

Chemical Name

Inorganic Salt Solution

Recommended Use

Various Industrial Applications

Manufacturer Information

MINERAL RESEARCH & DEVELOPMENT
5910 Pharr Mill Road
Harrisburg, NC 28075

Phone: 704-454-4811
FAX: 704-454-7390
CHEMTREC: (800) 424-9300
US and Canadian Shipping Only- 1-703-527-3887

General Comments

NOTE: Emergency telephone numbers are to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure, or accident involving chemicals. All non-emergency questions should be directed to customer service.

*** Section 2 – Hazard Identification ***

GHS Classification

Specific Target Organ Toxicity - Single Exposure, Category 1
Specific Target Organ Toxicity - Repeated Exposure, Category 1
Hazardous to Aquatic Life – Acute, Category 1
Hazardous to Aquatic Life – Chronic, Category 1
Skin Corrosion, Category 1A
Serious Eye Damage/Eye Irritation, Category 2B
Germ Cell Mutagenicity, Category 2

GHS Label Elements

Symbol(s)



Signal Word

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Danger

Hazard Statements

Causes severe skin burns and eye damage.
Causes eye irritation.
Suspected of causing genetic defects.
Causes damage to organs.
Causes damage to organs through prolonged or repeated exposure.
Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Response

If exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (OR HAIR): Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

IF INHALED: If inhaled, remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

*** Section 3 - Composition / Information on Ingredients ***

| CAS # | Component | Percent |
|------------|--------------------|---------|
| 7732-18-5 | Water | 0-77 |
| 7646-85-7 | Zinc chloride | 20-80 |
| 12125-02-9 | Ammonium chloride | 3-30 |
| 7647-01-0 | Hydrochloric Acid | 0-5 |
| 7447-40-7 | Potassium chloride | 0-2 |

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Component Information/Information on Non-Hazardous Components

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This product is considered hazardous under the criteria specified in the Canadian Workplace Hazardous Materials Information System (WHMIS).

*** Section 4 - First Aid Measures ***

Description of Necessary Measures

Eyes Contact

IF IN EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention at once.

Skin Contact

IF ON SKIN (or hair): Flush with large amounts of water while removing contaminated clothing. Continue flushing skin with water for 15 minutes. If skin irritation occurs: Get medical advice/attention. Contaminated leather articles, including shoes, that cannot be decontaminated should be discarded.

Ingestion

IF SWALLOWED: If material is ingested, immediately contact a physician or poison control center. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.

Inhalation

IF INHALED: Immediately remove the affected person to fresh air. If the affected person is not breathing, have qualified personnel apply artificial respiration. Do NOT perform mouth-to-mouth resuscitation. Call a physician immediately.

First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

This product is an aqueous solution which will not burn.

Hazardous Combustion Products

Decomposition may yield zinc compounds, hydrogen chloride, ammonia, nitrogen oxides, and chlorine.

Extinguishing Media

Dry chemical, foam, carbon dioxide, water fog.

Fire Fighting Equipment/Instructions

This product is corrosive, and presents a severe contact hazard to fire-fighters. Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products. If this product is involved in a fire, fire run-off water should be contained to prevent possible environmental damage.



Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

NFPA Ratings: Health: 3 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

*** Section 6 - Accidental Release Measures ***

Containment Procedures

Stop the flow of material, if this is without risk. Wear appropriate protective equipment and clothing during clean up. Contain the discharged material and dike the spilled material where possible. Prevent entry into sewers, drains, underground or confined spaces, water intakes and waterways.

Clean-Up Procedures

Wear appropriate protective equipment and clothing during clean-up. Avoid the generation of dusts during clean-up. Sweep up or vacuum. Shovel material into appropriate container for disposal. If necessary, neutralize remaining area with sodium bicarbonate or other acid neutralizing agent and triple rinse with water. Do not allow the spilled product to enter public drainage system or open water courses.

Evacuation Procedures

Isolate area. Keep unnecessary personnel away.

Special Procedures

Isolate exposure. Wear appropriate personal protective equipment. Follow all Local, State, Federal and Provincial regulations for disposal.

*** Section 7 - Handling and Storage ***

Handling Procedures

Do not get this material in your eyes, on your skin, or on your clothing. Avoid breathing vapors or mists of this product. Wash thoroughly after handling. Do not eat, drink or use tobacco products when handling this material. Use this product with adequate ventilation. Launder work clothes frequently. Open containers slowly, on a stable surface. Containers of this product must be properly labeled. Empty containers may contain residual liquid or vapors. Empty containers should be handled with care.

Storage Procedures

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see SECTION 10: Stability and Reactivity). Material should be stored in secondary containers, or in a diked area, as appropriate. Keep container tightly closed when not in use. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged.

*** Section 8 - Exposure Controls / Personal Protection ***

Component Exposure Limits

Hydrochloric Acid (7647-01-0)

ACGIH: 2 ppm Ceiling

OSHA (Final): 5 ppm Ceiling; 7 mg/m³ Ceiling

OSHA (Vacated): 5 ppm Ceiling; 7 mg/m³ Ceiling

NIOSH: 5 ppm Ceiling; 7 mg/m³ Ceiling

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Alberta: 5 ppm Ceiling; 7.5 mg/m³ Ceiling
British Columbia: 2 ppm Ceiling
Manitoba: 5 ppm Ceiling; 7 mg/m³ Ceiling
New Brunswick: 5 ppm Ceiling; 7.5 mg/m³ Ceiling
NW Territories: 5 ppm Ceiling; 7.5 mg/m³ Ceiling
Nova Scotia: 2 ppm Ceiling
Nunavut: 5 ppm Ceiling; 7.5 mg/m³ Ceiling
Ontario: 2 ppm CEV
Quebec: 5 ppm Ceiling; 7.5 mg/m³ Ceiling
Saskatchewan: 7.5 mg/m³ Ceiling; 5 ppm Ceiling
Yukon: 5 ppm Ceiling; 7 mg/m³ Ceiling

Zinc chloride (7646-85-7)

ACGIH: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
OSHA (Final): 1 mg/m³ TWA (fume)
OSHA (Vacated): 1 mg/m³ TWA
2 mg/m³ STEL
NIOSH: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Alberta: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
British Columbia: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Manitoba: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
New Brunswick: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
NW Territories: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Nova Scotia: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Nunavut: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Ontario: 1 mg/m³ TWAEV (fume)
2 mg/m³ STEV (fume)
Quebec: 1 mg/m³ TWAEV (fume)
Saskatchewan: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)
Yukon: 1 mg/m³ TWA (fume)
2 mg/m³ STEL (fume)

Ammonium chloride (12125-02-9)

ACGIH: 10 mg/m³ TWA (fume)
20 mg/m³ STEL (fume)
OSHA (Vacated): 10 mg/m³ TWA
20 mg/m³ STEL
NIOSH: 10 mg/m³ TWA (fume)
20 mg/m³ STEL (fume)
Alberta: 10 mg/m³ TWA (fume)
20 mg/m³ STEL (fume)
British Columbia: 10 mg/m³ TWA (fume)

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

| | |
|-----------------|-----------------------------------|
| | 20 mg/m ³ STEL (fume) |
| Manitoba: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| New Brunswick: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| NW Territories: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| Nova Scotia: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| Nunavut: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| Ontario: | 10 mg/m ³ TWAEV (fume) |
| | 20 mg/m ³ STEV (fume) |
| Quebec: | 10 mg/m ³ TWAEV (fume) |
| | 20 mg/m ³ STEV (fume) |
| Saskatchewan: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |
| Yukon: | 10 mg/m ³ TWA (fume) |
| | 20 mg/m ³ STEL (fume) |

Engineering Controls

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses; chemical goggles (if splashing is possible).

Personal Protective Equipment: Skin

Use impervious gloves. Use of an impervious apron is recommended.

Personal Protective Equipment: Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapors or mists, appropriate approved NIOSH respiratory protection must be provided. Respirators should be selected by and used under the direction of a trained health and safety professional following the requirements found in OSHA's respirator standard (29 CFR 1901.134) and ANSI's standard for respiratory protection (Z88.2-1992), applicable U.S. regulations, or the Canadian CSA Standard Z94.4-93 and applicable standards of Canadian Provinces. A written respiratory protection program, including provisions for medical certification, training, fit-testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage, must be implemented.

Personal Protective Equipment: General

Eyewash fountains and emergency showers are required. An emergency spill response will necessitate the use of more stringent personal protective equipment.

*** Section 9 - Physical & Chemical Properties ***

Appearance: Light yellow liquid

Odor: Odorless

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

| | | | |
|--|-----------------|---|------------------------|
| Physical State: | Liquid | Odor Threshold: | Not Applicable |
| Vapor Pressure: | 23.8 mm Hg | pH: | <2.0 |
| Vapor Density: | <1.0 | Specific Gravity: | 1.50-1.55@ 59°F (15°C) |
| Boiling Point / Boiling Range: | >212°F (>100°C) | Evaporation Rate: | Not available |
| Melting Point / Freezing Point: | Not available | Relative Density: | Not available |
| Solubility (H₂O): | Soluble | Auto-ignition Temperature: | Not available |
| Flash Point: | Not Flammable | Decomposition Temperature: | Not available |
| Upper Flammable Limit (UFL): | Not Applicable | Lower Flammable Limit (LFL): | Not Applicable |
| Viscosity: | Not available | Partition Coefficient (n-octanol / water): | Not available |
| Flammability: | Not available | | |

*** Section 10 - Chemical Stability & Reactivity Information ***

Chemical Stability

Stable under normal conditions.

Chemical Stability: Conditions to Avoid

Avoid contact with incompatible materials.

Incompatibility

This product is incompatible with strong bases, strong oxidizing agents, alkali metals and their carbonate, lead and silver salts. Corrosive to metals.

Hazardous Decomposition

Decomposition may yield zinc compounds, hydrogen chloride, ammonia, nitrogen oxides, and chlorine.

Hazardous Polymerization

Will not occur.

*** Section 11 - Toxicological Information ***

Acute Toxicity

Acute exposure can cause severe irritation and burns of the eyes, skin, gastrointestinal tract and respiratory tract.

Zinc chloride is an eye, skin and respiratory system irritant. Inhalation of zinc fumes may result in temporary metal fume fever. Other symptoms such as slight leukocytosis, respiratory disease and hypocalcemia have been reported from occupational exposure to zinc compounds.

Component Analysis - LD50/LC50

Water (7732-18-5)

Oral LD50 Rat: >90 mL/kg

Zinc chloride (7646-85-7)

Oral LD50 Rat: 350 mg/kg
50 mg/m³ IDLH (fume)

Ammonium chloride (12125-02-9)

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Oral LD50 Rat: 1,410 mg/kg

Hydrochloric Acid (7647-01-0)

Inhalation LC50 Rat: 3,124 ppm/1H; Oral LD50 Rat: 700 mg/kg; Dermal LD50 Rabbit: >5,010 mg/kg
50 ppm IDLH

Information on Likely Routes of Exposure

Inhalation

This product is irritating to the respiratory system. Damage to the tissues of the respiratory system may occur, such as burns and ulcers, especially after prolonged overexposures or overexposures to high concentrations of this product. Additional inhalation symptoms may include the following: choking, coughing, and difficulty breathing. Severe inhalation overexposures can lead to pulmonary edema, pneumonitis, and death.

Ingestion

If ingested, this product will immediately cause burns to the mouth, throat, esophagus and possibly the digestive tract. Overexposure symptoms include: drowsiness, confusion, difficulty swallowing, a burning sensation in the esophagus and stomach, intense thirst, nausea, abdominal pain, vomiting, diarrhea, stomach perforation, bloody stools or urine, convulsions, and collapse. Large quantity ingestion may be fatal.

Skin Contact

This product may be severely irritating to the skin or cause burns. Depending on the duration of skin contact, skin overexposures will cause reddening, discomfort, irritation, ulceration, and chemical burns. Chemical burns can result in blistering of the skin and scarring.

Eye Contact

Contact with the eyes can cause severe irritation or burning of eyes. Overexposure will cause irritation or burns, depending on duration, pain, redness, and may result in blindness.

Immediate Effects

Causes severe irritation or burns to the eyes, skin, gastrointestinal tract, and respiratory system.

Delayed Effects

Prolonged or repeated skin contact may result in redness, burning sensation or dermatitis.

Hydrogen chloride or hydrochloric acid is a corrosive acid. Chronic exposure may be associated with changes in pulmonary function, chronic bronchitis, dermatitis, erosion of dental enamel, conjunctivitis and upper respiratory tract abnormalities.

Medical Conditions Aggravated by Exposure

Pre-existing eye, skin and/or respiratory tract conditions.

Irritation/Corrosivity Data

Respiratory tract irritation, skin irritation, eye irritation

Respiratory Sensitization

No data available.

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Dermal Sensitization

No data available for the mixture

Germ Cell Mutagenicity

No data available for the mixture.

Carcinogenicity

Component Carcinogenicity

Hydrochloric Acid (7647-01-0)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Monograph 54 [1992] (Group 3 (not classifiable))

Reproductive Toxicity

No data available for the mixture.

Specific Target Organ Toxicity - Single Exposure

No information available.

Specific Target Organ Toxicity - Repeated Exposure

No information available.

Aspiration Hazard

No information available.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

Due to the acidic nature of this product, a release of this product in a river or other body of water (especially in large volumes) will kill fish and other aquatic life.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Ammonium chloride (12125-02-9)

| Test & Species | | Conditions |
|--------------------------------|----------|------------|
| 24 Hr LC50 Lepomis macrochirus | 725 mg/L | |
| 96 Hr LC50 Cyprinus carpio | 209 mg/L | static |
| 24 Hr EC50 water flea | 202 mg/L | |

Hydrochloric Acid (7647-01-0)

| Test & Species | | Conditions |
|--------------------------------|----------|------------|
| 48 Hr LC50 Lepomis macrochirus | 3.6 mg/L | |
| 96 Hr LC50 Gambusia affinis | 282 mg/L | |

Environmental Fate

The components of this product are relatively stable under ambient, environmental conditions.

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

*** Section 13 - Disposal Considerations ***

US EPA Waste Number & Descriptions

A: General Product Information

Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. As packaged this product is a D002 corrosive waste [40 CFR 261.21(a)(4)]; applicable to wastes consisting only of this product.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

*** Section 14 - Transportation Information ***

US DOT Information

Shipping Name: Corrosive liquid, acidic, inorganic, n.o.s. (Zinc chloride, Ammonium chloride, Hydrochloric acid)

UN/NA #: UN3264 **Hazard Class:** 8 **Packing Group:** III

Required Label(s): CORROSIVE

ERG: #154



Canada Transportation of Dangerous Goods Information

Shipping Name: Corrosive liquid, acidic, inorganic, n.o.s. (Zinc chloride, Ammonium chloride, Hydrochloric acid)

UN/NA #: UN3264 **Hazard Class:** 8 **Packing Group:** III

Required Label(s): CORROSIVE



Shipping Name: Corrosive liquid, acidic, inorganic, n.o.s. (Zinc chloride, Ammonium chloride, Hydrochloric acid)

UN/NA #: UN3264 **Hazard Class:** 8 **Packing Group:** III

Required Label(s): CORROSIVE

EmS: F-A, S-B



*** Section 15 - Regulatory Information ***

US Federal Regulations

Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Zinc chloride (7646-85-7)

CERCLA: 1,000 lb final RQ; 454 kg final RQ

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

Ammonium chloride (12125-02-9)

CERCLA: 5,000 lb final RQ; 2270 kg final RQ

Hydrochloric Acid (7647-01-0)

SARA 302: 500 lb TPQ (gas only)

SARA 313: 1.0 % de minimis concentration (acid aerosols including mists, vapors, gas, fog, and other airborne forms of any particle size)

CERCLA: 5,000 lb final RQ; 2,270 kg final RQ

SARA 311/312: Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactive: No

Federal Insecticide, Fungicide, and Rodenticide Act

This material contains the following chemicals present on either the Listing of Pesticide Chemicals (40 CFR 180) or Pesticides Classified for Restricted Use as listed by FIFRA :

Ammonium chloride (12125-02-9)

FIFRA Section number 180.910; Section number 180.940

Hydrochloric Acid (7647-01-0)

FIFRA Section number 180.910

State Regulations

A: General Product Information

Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

| Component | CAS | CA | MA | MN | NJ | PA | RI |
|-------------------|------------|-----|-----|-----|-----|-----|-----|
| Zinc chloride | 7646-85-7 | Yes | Yes | Yes | Yes | Yes | Yes |
| Ammonium chloride | 12125-02-9 | Yes | Yes | Yes | Yes | Yes | Yes |
| Hydrochloric Acid | 7647-01-0 | Yes | Yes | Yes | Yes | Yes | Yes |

No components are listed on the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65).

Component Analysis - WHMIS IDL

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which fall under WHMIS criteria specified in the Controlled Products Regulations and present above the threshold limits listed on the IDL. The following components are listed on the IDL;

| Component | CAS # | Minimum Concentration |
|-------------------|------------|-----------------------|
| Zinc chloride | 7646-85-7 | 1 % |
| Ammonium chloride | 12125-02-9 | 1 % |
| Hydrochloric Acid | 7647-01-0 | 1 % |

WHMIS Classification

Safety Data Sheet

Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU

MRD-218

C, D2B

Additional Regulatory Information

A: General Product Information

No additional information available.

B: Component Analysis - Inventory

| Component | CAS # | TSCA | DSL | NDSL | EINECS | AU | MITI | PH | KR | ELINCS | CN |
|-------------------|------------|------|-----|------|--------|-----|------|-----|-----|--------|-----|
| Water | 7732-18-5 | Yes | Yes | No | Yes | Yes | Yes | No | Yes | No | Yes |
| Zinc chloride | 7646-85-7 | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | No | Yes |
| Ammonium chloride | 12125-02-9 | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | No | Yes |
| Hydrochloric Acid | 7647-01-0 | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | No | Yes |

*** Section 16 - Other Information ***

Summary of Changes

New SDS: 12/19/2014 v1.0; Revised 05/04/2015 v1.5; Revised 06/08/2015, Revised 7/10/2015, Revised 8/31/2015 v1.8

Key / Legend

ACGIH = American Conference of Governmental Industrial Hygienists; **AU** = Australia; **BOD** - Biochemical Oxygen Demand; **C** - Celsius; **CA** - Canada; **CAS** = Chemical Abstracts Service; **CERCLA** = Comprehensive Environmental Response, Compensation, and Liability Act; **CFR** = Code of Federal Regulations; **CN** = China; **CPR** = Controlled Products Regulations; **DOT** = Department of Transportation; **DSL** = Domestic Substances List; **EINECS** = European Inventory of Existing Commercial Chemical Substances; **ELINCS** = European List of Notified Chemical Substances; **EPA** = Environmental Protection Agency; **ERG** = Emergency Response Guide; **EU** = European Union; **F** - Fahrenheit; **HEPA** = High Efficiency Particulate Air; **HMIS** = Hazardous Material Information System; **HPV** – High Production Volume Chemical (EU); **IARC** = International Agency for Research on Cancer; **IATA** = International Air Transport Association; **ICL** – In Commerce List (Canada); **IDL** - Ingredient Disclosure List; **IDLH** - Immediately Dangerous to Life and Health; **IMDG** = International Maritime Dangerous Goods; **JP** = Japan; **KR** = Korea; **LEL** - Lower Explosive Limit; **MITI** = Japan Ministry of International Trade and Industry; **mg/Kg** = milligrams per Kilogram; **mg/L** = milligrams per Liter; **mg/m³** = milligrams per Cubic Meter; **MSHA** = Mine Safety and Health Administration; **MX** = Mexico; **NA** = Not Applicable or Not Available; **NFPA** = National Fire Protection Association; **NIOSH** = National Institute for Occupational Safety and Health; **NJTSR** = New Jersey Trade Secret Registry; **NTP** = National Toxicology Program; **NZ** = New Zealand; **OSHA** = Occupational Safety and Health Administration; **PH** = Philippines; **RCRA** = Resource Conservation & Recovery Act; **SARA** = Superfund Amendments and Reauthorization Act; **STEL** = Short Term Exposure Limit; **STELV** = Short Term Exposure Limit Exposure Values; **TDG** = Transport Dangerous Goods; **TSCA** = Toxic Substances Control Act; **TWA** - Time Weighted Average; **TWAEV** = Time Weighted Average Exposure Values; **UEL** - Upper Explosive Limit; **US** - United States; **WHMIS** = Workplace Hazardous Materials Information System.

Other Information

Disclaimer: Supplier gives no warranty of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser will make his own tests to determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental and/or consequential property damage arising out of the use of this product. No information provided shall be deemed to be a recommendation

Safety Data Sheet

**Preact Galvanizing Flux Solution SF-L, SF-LB,
SF-LB 60, BG-L, BG-LW, CN-L, CN-SL, MW, DB-L, EVF-L, GPS-W, GPS-AN, SFLU**

MRD-218

to use any product in conflict with any existing patent rights. Read the Safety Data Sheet before handling product.

End of Sheet MRD-218